FILT'RAY 1-month shower filter

Ref. AT030711

Sterile



DESCRIPTION

FILT'RAY 1-month shower filter

Ref. AT030711

AQUATOOLS anti-Legionella and all-germ shower filter.

Device made from MBS.

Membrane type: tubular microfiltration.

Membrane made from polyethylene.

Pore cut-off threshold: 0.1μm nominal and 0.2μm absolute sterilising grade.

Filtration flow rate: 9 lpm at 3 bar and 6 lpm at 1 bar

(filter only, excludes any flow rate restriction in the shower).

Maximum upstream pressure at the point-of-use: 5 bar.

Maximum lifespan: 1 month from installation.

Withstands thermal shocks: 70°C for 30 minutes.

Withstands chemical shocks: active chlorine levels up to 100 ppm

for 1 hour (cumulative total).

Sterile filter.

FILT'RAY 2G sterile disposable water filters are:

CE marked Class I Medical Devices in Europe that comply with directive 93/42/CEE;

Class II Medical Devices in the U.S.A. with FDA-510(K) clearance;

Class I Medical Devices in Canada that comply with SOR/98-282.

Packaged in boxes of 10, each filter is individually wrapped and sterile.

ADVANTAGES



Anti-Legionella and all-germ



Lifespan: 1 month from installation



Bubl'air Wash: longer filter life



Rapid installation with no tools required

TECHNICAL CHARACTERISTICS

FILT'RAY 1-month shower filter - Ref. AT030711

Technology	Point-of-use filtration
Height	70mm
Length	225mm
Flow rate	9 lpm at 3 bar, 6 lpm at 1 bar
Lifespan	1 month
Norms	ACS (

