

FILT'RAY 1-month tap filter

Ref. AT030728

Non-sterile



DESCRIPTION

FILT'RAY 1-month tap filter

Ref. AT030728

 $\label{eq:AQUATOOLS} \textbf{AQUATOOLS} \ \textbf{anti-Legionella} \ \textbf{and} \ \textbf{all-germ} \ \textbf{tap} \ \textbf{filter}, \ \textbf{shower} \ \textbf{spray}.$

Device made from MBS.

Membrane type: tubular microfiltration.

Membrane made from polyethylene.

Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.

Filtration flow rate: 6.3 lpm at 3 bar and 2.2 lpm at 1 bar (filter only, excludes any flow rate restriction in the tap).

Maximum upstream pressure at the point-of-use: 5 bar.

Maximum lifespan: 1 month from installation. Withstands thermal shocks: 70°C for 30 minutes.

Withstands chemical shocks: active chlorine levels up to 100 ppm

for 1 hour (cumulative total).

Non-sterile filter.

CE marked Class I medical device.

Packaged in boxes of 10, each filter is individually wrapped and sterile.

TECHNICAL CHARACTERISTICS

FILT'RAY 1-month tap filter - Ref. AT030728

Technology	Point-of-use filtration
Height	72mm
Length	75mm
Flow rate	6.3 lpm at 3 bar, 2.2 lpm at 1 bar
Lifespan	1 month
Norms	ACS (€ WRAS

ADVANTAGES



Anti-Legionella and all-germ



Lifespan: 1 month from installation



Bubl'air Wash: longer filter life



Rapid installation with no tools required

