FILT'RAY tap filter, 4-months

Ref. AT030740

Non-sterile

DESCRIPTION

FILT'RAY tap filter, 4-months
Ref. AT030740

AQUATOOLS anti-Legionella and all-germ tap filter.
Device made from MBS.
Membrane type: tubular microfiltration.
Membrane made from polyethylene.
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
Filtration flow rate: 6 lpm at 3 bar and 4 lpm at 1 bar
(filter only, excludes any flow rate restriction in the tap).
Maximum upstream pressure at the point-of-use: 5 bar.
Maximum lifespan: 4 months from installation.
Withstands thermal shocks: 70°C for 30 minutes.
Withstands chemical shocks: active chlorine levels up to 100 ppm
for 4 hours (cumulative total).
Non-sterile filter.
CE marked Class I medical device.
Packaged in boxes of 10.

ADVANTAGES

- Anti-Legionella and all-germ
- Lifespan 4 months from installation
- Bubl'air Wash: longer filter life
- Rapid installation with no tools required

TECHNICAL CHARACTERISTICS

FILT'RAY tap filter, 4-months - Ref. AT030740

Technology	Point-of-use filtration
Height	72mm
Length	75mm
Flow rate	6 lpm at 3 bar and 4 lpm at 1 bar
Lifespan	4 months
Norms	ACS CE WRAS



© AQUATOOLS