

FILT'RAY 1-month tap filter

Ref. AT030727

Non-sterile



DESCRIPTION

FILT'RAY 1-month tap filter

Ref. AT030727

AQUATOOLS anti-Legionella and all-germ tap filter.
Device made from ABS.
Membrane type: tubular microfiltration.
Membrane made from polyethylene.
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
Filtration flow rate: 6.3 lpm at 3 bar and 2.2 lpm at 1 bar (filter only, excludes any flow rate restriction in the tap).
Maximum upstream pressure at the point-of-use: 5 bar.
Maximum lifespan: 1 month from installation.
Resistance to thermal shocks: 70°C for 30 minutes.
Resistance to chemical shocks: active chlorine levels up to 100 ppm for 1 hour (cumulative total).
Non-sterile filter.
CE marked class I medical device.
Packaged in boxes of 10.

TECHNICAL CHARACTERISTICS

FILT'RAY 1-month tap filter - Ref. AT030727

Technology	Point-of-use filtration
Height	72mm
Length	75mm
Flow rate	6.3 lpm at 3 bar, 2.2 lpm at 1 bar
Lifespan	1 month
Norms	ACS CE 

ADVANTAGES



Anti-Legionella and all-germ



Lifespan: 1 month from installation



Bubl'air Wash: longer filter life



Rapid installation with no tools required

