

FILT'RAY 2G 1-month filter for fixed, wall-mounted showers

Ref. AT030767

Non-sterile



DESCRIPTION

FILT'RAY 2G 1-month filter for fixed, wall-mounted showers

Ref. AT030767

AQUATOOLS anti-Legionella and all-germ filter for fixed, wall-mounted showers (shower panels).
 Device made from MBS.
 Membrane type: tubular microfiltration.
 Membrane made from polyethylene.
 Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
 Filtration flow rate: 13.1 lpm at 3 bar and 3.9 lpm at 1 bar (filter only, excludes any flow rate restriction in the shower).
 Maximum upstream pressure at the point-of-use: 5 bar.
 Maximum lifespan: 1 month from installation.
 Withstands thermal shocks: 70°C for 30 minutes.
 Withstands chemical shocks: active chlorine levels up to 100 ppm for 1 hour (cumulative total).
 Non-sterile filter.
 CE marked Class I medical device.
 Packaged in boxes of 10.

ADVANTAGES



Anti-Legionella and all-germ



Lifespan: 1 month from installation



Bubl'air Wash: longer filter life



Rapid installation with no tools required

TECHNICAL CHARACTERISTICS

FILT'RAY 2G 1-month filter for fixed, wall-mounted showers - Ref. AT030767

Technology	Point-of-use filtration
Height	72mm
Length	75mm
Flow rate	13.1 lpm at 3 bar, 3.9 lpm at 1 bar
Lifespan	1 month
Norms	ACS CE JWRAS

