

FILT'RAY 2G 1-month filter for fixed, wall-mounted showers

Ref. AT030767

Non-sterile



DESCRIPTION

FILT'RAY 2G 1-month filter for fixed, wall-mounted showers

Ref. AT030767

AQUATOOLS anti-Legionella and all-germ filter for fixed, wall-mounted showers (shower panels).

Device made from MBS.

Membrane type: tubular microfiltration.

Membrane made from polyethylene.

Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.

Filtration flow rate: 13.1 lpm at 3 bar and 3.9 lpm at 1 bar

(filter only, excludes any flow rate restriction in the shower).

Maximum upstream pressure at the point-of-use: 5 bar.

Maximum lifespan: 1 month from installation.

Withstands thermal shocks: 70°C for 30 minutes.

Withstands chemical shocks: active chlorine levels up to 100 ppm for 1 hour (cumulative total).

Non-sterile filter.

CE marked Class I medical device.

Packaged in boxes of 10.

ADVANTAGES



Anti-Legionella and all-germ



Lifespan: 1 month from installation



Bubl'air Wash: longer filter life



Rapid installation with no tools required

TECHNICAL CHARACTERISTICS

FILT'RAY 2G 1-month filter for fixed, wall-mounted showers - Ref. AT030767

Technology	Point-of-use filtration
Height	72mm
Length	75mm
Flow rate	13.1 lpm at 3 bar, 3.9 lpm at 1 bar
Lifespan	1 month
Norms	ACS CE JWRAS

