

FILT'RAY 3-month filter for fixed, wall-mounted showers

Ref. AT030741

Non-sterile

DESCRIPTION


FILT'RAY 3-month filter for fixed, wall-mounted showers Ref. AT030741

AQUATOOLS anti-Legionella and all-germ filter for fixed, wall-mounted showers (shower panels). Device made from MBS. Membrane type: tubular microfiltration. Membrane made from polyethylene. Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade. Filtration flow rate: 9 lpm at 3 bar and 6 lpm at 1 bar (filter only, excludes any flow rate restriction in the shower). Maximum upstream pressure at the point-of-use: 5 bar. Maximum lifespan: 3 months from installation. Withstands thermal shocks: 70°C for 30 minutes. Withstands chemical shocks: active chlorine levels up to 100 ppm for 3 hours (cumulative total). Non-sterile filter. CE marked Class I medical device. Packaged in boxes of 10.

TECHNICAL CHARACTERISTICS

FILT'RAY 3-month filter for fixed, wall-mounted showers - Ref. AT030741

Technology	Point-of-use filtration
Height	72mm
Length	75mm
Flow rate	9 lpm at 3 bar, 6 lpm at 1 bar
Lifespan	3 months
Norms	ACS (E MRAS



equertools

ADVANTAGES



Anti-Legionella and all-germ



Lifespan: 3 months from installation



Bubl'air Wash: longer filter life



Rapid installation with no tools required