

FILT'RAY Compact 4-month shower head filter

Ref. AT30461

Non-sterile

DESCRIPTION

Device made from ABS.

(cumulative total).

Ref. AT30461

ADVANTAGES FILT'RAY Compact 4-month shower head filter Anti-Legionella and all-germ AQUATOOLS anti-Legionella and all-germ shower filter. Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.

Space saving Lifespan: 4 months after installation



Non-sterile filter. CE Class I medical device. Weight: empty filter 133g / full filter 259g. Packaged in boxes of 10 units.

Membrane type: tubular microfiltration. Membrane made from polyethylene.

Qualified water volume per duration of use: 12,000 litres.

(filter only, excludes any flow rate restriction in the tap).

Maximum upstream pressure at the point-of-use: 5 bar. Maximum lifespan: 4 months after installation. Resistance to thermal shocks: 70°C for 30 minutes.

Filtration flow rate: 6.5 lpm at 1 bar, 11.8 lpm at 3 bar and 14.2 lpm at 5 bar

Resistance to chemical shocks: active chlorine levels up to 100 ppm for 4 hours

TECHNICAL CHARACTERISTICS

FILT'RAY Compact 4-month shower head filter - Ref. AT30461

Connector	M1/2"
Technology	Point-of-use filtration
Height	77mm
Length	194mm
Flow rate	6.5 lpm at 1 bar, 11.2 lpm at 3 bar and 13.2 lpm at 5 bar
Diameter	56mm
Lifespan	4 months
Norms	ACS (C WRAS BWGL

