

# FILT'RAY 4-month shower head filter

Ref. AT30461

Non-sterile



## DESCRIPTION

**FILT'RAY 4-month shower head filter**

**Ref. AT30461**

AQUATOOLS anti-Legionella and all-germ shower filter.  
Device made from ABS.  
Membrane type: tubular microfiltration.  
Membrane made from polyethylene.  
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.  
Qualified water volume per duration of use: 12,000 litres.  
Filtration flow rate: 6.5 lpm at 1 bar, 11.8 lpm at 3 bar and 14.2 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap).  
Maximum upstream pressure at the point-of-use: 5 bar.  
Maximum lifespan: 4 months after installation.  
Resistance to thermal shocks: 70°C for 30 minutes.  
Resistance to chemical shocks: active chlorine levels up to 100 ppm for 4 hours (cumulative total).  
Non-sterile filter.  
CE Class I medical device.  
Weight: empty filter 133g / full filter 259g.  
Packaged in boxes of 10 units.

## TECHNICAL CHARACTERISTICS

**FILT'RAY 4-month shower head filter - Ref. AT30461**

Connector	M1/2"
Technology	Point-of-use filtration
Height	77mm
Length	194mm
Flow rate	6.2 lpm at 1 bar, 11.2 lpm at 3 bar and 13.2 lpm at 5 bar
Diameter	56mm
Lifespan	4 months
Norms	ACS CE WWRAS KTW BWGL

## ADVANTAGES



Anti-Legionella and all-germ



Space saving



Lifespan: 4 months after installation



Quick to install without tools

