

FILT'RAY Compact 1-month tap filter

Ref. AT30150

Non-sterile



DESCRIPTION

FILT'RAY Compact 1-month tap filter

Ref. AT30150

AQUATOOLS anti-Legionella and all-germ tap filter.

Device made from ABS.

Membrane type: tubular microfiltration.

Membrane made from polyethylene.

Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade, shower spray.

Qualified water volume per duration of use: 3,000 litres.

Filtration flow rate: 2.7 lpm at 1 bar, 5.1 lpm at 3 bar and 7 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap).

Space saving, suitable for taps with a low spout height: H. 38mm, Ø 46mm.

Controlled management of retro-contamination: protective skirt and angled connector for optimal positioning (filter position can be adjusted so the water does not flow directly on to the waste).

Maximum upstream pressure at the point-of-use: 5 bar.

Maximum lifespan: 1 month after installation.

Resistance to thermal shocks: 70°C for 30 minutes.

Resistance to chemical shocks: active chlorine levels up to 100 ppm for 1 hour (cumulative total).

Non-sterile filter.

Medical device CE Class I.

Reference for a single unit. Must be ordered in multiples of 10.

Packaged in boxes of 10 units.

TECHNICAL CHARACTERISTICS

FILT'RAY Compact 1-month tap filter - Ref. AT30150

Technology	Point-of-use filtration
Height	38mm
Flow rate	2.7 lpm at 1 bar, 5.1 lpm at 3 bar and 7 lpm at 5 bar
Diameter	46mm
Lifespan	1 month
Norms	ACS KTW BWGL WRAS CE

ADVANTAGES



Anti-Legionella and all-germ



Space saving



Optimised position: angled connection



Lifespan: 1 month after installation

