# FILT'RAY Compact 1-month tap filter

Ref. AT30150

Non-sterile



## DESCRIPTION

**FILT'RAY Compact 1-month tap filter**

**Ref. AT30150**

AQUATOOLS anti-Legionella and all-germ tap filter.
Device made from ABS.
Membrane type: tubular microfiltration.
Membrane made from polyethylene.
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade, shower spray.
Qualified water volume per duration of use: 3,000 litres.
Filtration flow rate: 5.1 lpm at 3 bar (filter only, excludes any flow rate restriction in the tap).
Space saving, suitable for taps with a low spout height: H. 38mm, Ø 46mm.
Controlled management of retro-contamination: protective skirt and angled connector for optimal positioning (filter position can be adjusted so the water does not flow directly on to the waste).
Maximum upstream pressure at the point-of-use: 5 bar.
Maximum lifespan: 1 month after installation.
Resistance to thermal shocks: 70°C for 30 minutes.
Resistance to chemical shocks: active chlorine levels up to 100 ppm for 1 hour (cumulative total).
Non-sterile filter.
Medical device CE Class I.
Reference for a single unit. Must be ordered in multiples of 10.
Packaged in boxes of 10 units.


## ADVANTAGES

- Anti-Legionella and all-germ
- Space saving
- Optimised position: angled connection
- Lifespan: 1 month after installation

## TECHNICAL CHARACTERISTICS

**FILT'RAY Compact 1-month tap filter - Ref. AT30150**

| | |
|---|---|
| Technology | Point-of-use filtration |
| Height | 38mm |
| Flow rate | 2.7 lpm at 1 bar, 5.1 lpm at 3 bar and 7 lpm at 5 bar |
| Diameter | 46mm |
| Lifespan | 1 month |
| Norms | ACS KTW BWGL WRAS CE |




© AQUATOOLS