

# FILT'RAY Compact 1-month tap filter

Ref. AT30151

Non-sterile



## DESCRIPTION

**FILT'RAY Compact 1-month tap filter**

**Ref. AT30151**

AQUATOOLS anti-Legionella and all-germ tap filter, laminar flow.  
Device made from ABS.  
Membrane type: tubular microfiltration.  
Membrane made from polyethylene.  
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.  
Qualified water volume per duration of use: 3,000 litres.  
Filtration flow rate: 2.7 lpm at 1 bar, 5.1 lpm at 3 bar and 7 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap).  
Space saving, suitable for taps with a low spout height: H. 38mm, Ø 46mm.  
Controlled management of retro-contamination: protective skirt and angled connector for optimal positioning (filter position can be adjusted so the water does not flow directly on to the waste).  
Maximum upstream pressure at the point-of-use: 5 bar.  
Maximum lifespan: 1 month after installation.  
Resistance to thermal shocks: 70°C for 30 minutes.  
Resistance to chemical shocks: active chlorine levels up to 100 ppm for 1 hour (cumulative total).  
Non-sterile filter.  
CE Class I medical device.  
Reference for a single unit. Must be ordered in multiples of 10.  
Packaged in boxes of 10 units.

## ADVANTAGES



Anti-Legionella and all-germ



Space saving



Optimised position: tilted connector



Lifespan: 1 month after installation

## TECHNICAL CHARACTERISTICS

**FILT'RAY Compact 1-month tap filter - Ref. AT30151**

Technology	Point-of-use filtration
Height	38mm
Flow rate	2.7 lpm at 1 bar, 5.1 lpm at 3 bar and 7 lpm at 5 bar
Diameter	46mm
Lifespan	1 month
Norms	ACS CE JWRAS KTW BWGL

