# FILT'RAY Compact 4-month tap filter

Ref. AT30451

Non-sterile

## DESCRIPTION

**FILT'RAY Compact 4-month tap filter**
**Ref. AT30451**

AQUATOOLS anti-Legionella and all-germ tap and wall-mounted shower filter, laminar flow.
Device made from ABS.
Membrane type: tubular microfiltration.
Membrane made from polyethylene.
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
Qualified water volume per duration of use: 12,000 litres.
Filtration flow rate: 4.6 lpm at 1 bar, 7.6 lpm at 3 bar and 9.4 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap).
Space saving, suitable for taps with a low spout height: H. 63mm, Ø 56mm.
Controlled management of retro-contamination: protective skirt and angled connector for optimal positioning (filter position can be adjusted so the water does not flow directly on to the waste).
Maximum upstream pressure at the point-of-use: 5 bar.
Maximum lifespan: 4 months after installation.
Resistance to thermal shocks: 70°C for 30 minutes.
Resistance to chemical shocks: active chlorine levels up to 100 ppm for 4 hours (cumulative total).
Non-sterile filter.
CE Class I medical device.
Reference for a single unit. Must be ordered in multiples of 10.
Packaged in boxes of 10 units.

## ADVANTAGES

- Anti-Legionella and all-germ
- Space saving
- Optimised position: tilted connector
- Lifespan: 4 months after installation

## TECHNICAL CHARACTERISTICS

**FILT'RAY Compact 4-month tap filter - Ref. AT30451**

| | |
|---|---|
| Technology | Point-of-use filtration |
| Height | 63mm |
| Flow rate | 4.6 lpm at 1 bar, 7.6 lpm at 3 bar and 9.4 lpm at 5 bar |
| Diameter | 56mm |
| Lifespan | 4 months |
| Norms | ACS CE WRAS KTW BWGL |




© AQUATOOLS