FILT'RAY 2G 3-month tap filter

Ref. AT030747

Sterile

DESCRIPTION

FILT'RAY 2G 3-month tap filter
Ref. AT030747

AQUATOOLS anti-Legionella and anti-germ tap filter, laminar flow.
Device made from MBS.
Membrane type: tubular microfiltration.
Membrane made from polyethylene.
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
Filtration flow rate: 6 lpm at 3 bar and 4 lpm at 1 bar (filter only, excludes any flow rate restriction in the tap).
Maximum upstream pressure at the point-of-use: 5 bar.
Maximum lifespan: 3 months after installation.
Resistance to thermal shocks: 70°C for 30 minutes.
Resistance to chemical shocks: active chlorine levels up to 100 ppm for 3 hours (cumulative total).
Sterile filter.
FILT'RAY 2G sterile disposable water filters are:
CE marked Class I Medical Devices in Europe that comply with directive 93/42/CEE;
Class II Medical Devices in the U.S.A. with FDA-510(K) clearance;
Class I Medical Devices in Canada that comply with SOR/98-282.
Packaged in boxes of 10 units and individually wrapped.

ADVANTAGES

- Anti-Legionella and all-germ
- Lifespan: 3 months from installation
- Bubl'air Wash: extends filter life
- Quick to install without tools

TECHNICAL CHARACTERISTICS

FILT'RAY 2G 3-month tap filter - Ref. AT030747

Technology	Point-of-use filtration
Height	72mm
Length	75mm
Flow rate	6 lpm at 3 bar and 4 lpm at 1 bar
Lifespan	3 months
Norms	CE WRAS ACS



© AQUATOOLS