FILT'RAY Compact 1-month tap filter

Ref. AT20150

Sterile



DESCRIPTION

FILT'RAY Compact 1-month tap filter

Ref. AT20150

AQUATOOLS anti-Legionella and all-germ tap filter, shower spray.
Device made from ABS.
Membrane type: tubular microfiltration.
Membrane made from polyethylene.
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
Qualified water volume per duration of use: 3,000 litres.
Filtration flow rate: 5.1 lpm at 3 bar (filter only, excludes any flow rate restriction in the tap).
Space saving, suitable for taps with a low spout height: H. 38mm, Ø 46mm.
Controlled management of retro-contamination: protective skirt and tilted connector for optimal positioning (filter position can be adjusted so the water does not flow directly on to the waste).
Maximum upstream pressure at the point-of-use: 5 bar.
Maximum lifespan: 1 month after installation.
Resistance to thermal shocks: 70°C for 30 minutes.
Resistance to chemical shocks: active chlorine levels up to 100 ppm for 1 hour (cumulative total).
Sterile filter.
Medical device CE Class Is.
Reference for a single unit. Must be ordered in multiples of 10.
Packaged in boxes of 10 units.


ADVANTAGES

- Anti-legionella and all-germ
- Space saving
- Optimised position: tilted connection
- Lifespan: 1 month after installation

TECHNICAL CHARACTERISTICS

FILT'RAY Compact 1-month tap filter - Ref. AT20150

Technology	Point-of-use filtration
Height	38mm
Flow rate	2.7 lpm at 1 bar, 5.1 lpm at 3 bar and 7 lpm at 5 bar
Diameter	46mm
Lifespan	1 month
Norms	ACS WRAS KTW BWGL



© AQUATOOLS