FILT'RAY Compact 2-month filter spout

Ref. AT30240

Non-sterile



DESCRIPTION

FILT'RAY Compact 2-month filter spout

Ref. AT30240

FILT'RAY Compact single use anti-Legionella and all-germ removable spout.
Can be installed instead of a removable spout (no need for any tools or to shut off the water supply).
Membrane type: tubular microfiltration.
Membrane made from polyethylene.
Pore cut-off threshold: 0.1µm nominal sterilising grade.
Filtration flow rate: 6 lpm at 3 bar (filter only, excludes any flow rate restriction in the tap).
Maximum upstream pressure at the point-of-use: 5 bar.
Maximum lifespan: 2 months after installation.
Compatible with and resistant to thermal and chemical shocks.
Non-sterile filter.
Weight: 40g.
Reference for a single unit. Must be ordered in multiples of 10.
Packaged in boxes of 10 units.


ADVANTAGES

- Anti-legionella and all-germ
- Easy to install without tools
- Lifespan: 2 months after installation
- Maintains drop height

TECHNICAL CHARACTERISTICS

FILT'RAY Compact 2-month filter spout - Ref. AT30240

Technology	Point-of-use filtration
Length	138mm
Flow rate	6 lpm
Norms	ACS WRAS KTW BWGL



© AQUATOOLS