

FILT'RAY Compact 2-month filter spout

Ref. AT30240

Non-sterile



DESCRIPTION

FILT'RAY Compact 2-month filter spout

Ref. AT30240

FILT'RAY Compact single use anti-Legionella and all-germ removable spout. Can be installed instead of DELABIE's removable BIOCLIP spouts (no need for any tools or to shut off the water supply).

Membrane type: tubular microfiltration.

Membrane made from polyethylene.

Pore cut-off threshold: 0.1µm nominal sterilising grade.

Filtration flow rate: 6 lpm at 3 bar (filter only, excludes any flow rate restriction in the tap).

Maximum upstream pressure at the point-of-use: 5 bar.

Maximum lifespan: 2 months after installation.

Compatible with and resistant to thermal and chemical shocks.

Non-sterile filter.

Weight: 40g.

Reference for a single unit. Must be ordered in multiples of 10.

Packaged in boxes of 10 units.

ADVANTAGES



Anti-legionella and all-germ



Easy to install without tools



Lifespan: 2 months after installation



Maintains drop height

TECHNICAL CHARACTERISTICS

FILT'RAY Compact 2-month filter spout - Ref. AT30240

Technology	Point-of-use filtration
Length	138mm
Flow rate	6 lpm
Norms	ACS 

