

# FILT&SWAP Inline filter

Ref. AT50671

0.2µm microfiltration



## DESCRIPTION

**FILT&SWAP** Inline filter

**Ref. AT50671**

FILT&SWAP inline anti-Legionella filter 0.2µm.  
 Microfiltration: Retains all bacteria and other particles larger than 0.2µm.  
 Filter cartridge can be replaced without changing the filter body.  
 Membrane surface area: 0.5m<sup>2</sup>.  
 Capacity: 18,000L.  
 Maximum lifespan: 6 months.  
 Filtration flow rate: 9 lpm (with integrated flow restrictor), 14 lpm (without flow restrictor) at 3 bar.  
 Materials: Body and filtration cartridge made of polypropylene. Filter cartridge plastic components made of ABS.  
 Temperature: 4 - 38°C.  
 Operating pressure: 0.5 - 10 bar.  
 Connection type: Tube or G3/8".  
 Compatible with and resistant to chemical shocks (active chlorine levels up to 100 ppm for 1 hour (cumulative total) and thermal shocks (70°C for 30 minutes).

## ADVANTAGES



Anti-Legionella



6 months

## TECHNICAL CHARACTERISTICS

**FILT&SWAP** Inline filter - Ref. AT50671

Supply	Tube or G3/8"
Length	235mm
Flow rate	9 lpm (with integrated flow restrictor), 14 lpm (without flow restrictor) at 3 bar
Diameter	82mm
Norms	

